

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number  
**WO 2004/095565 A1**

(51) International Patent Classification<sup>7</sup>: **H01L 21/336**,  
29/78, 29/165

(74) Agent: **ROCHE, Denis**; Société Civile SPID, 156 Boulevard Haussmann, F-75008 Paris (FR).

(21) International Application Number:  
PCT/IB2004/001254

(22) International Filing Date: 16 April 2004 (16.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0350127 24 April 2003 (24.04.2003) FR

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **EL-FARHANE, Rebha** [FR/FR]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 Paris (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SEMICONDUCTOR DEVICE COMPRISING EXTENSIONS PRODUCED FROM MATERIAL WITH A LOW MELTING POINT



(57) Abstract: A semiconductor device comprises a gate electrode (1) and a gate insulating layer (2) both surrounded by a spacer (3) and produced on a surface (S) of a substrate (100) of a first semiconductor material. The device also comprises a source region (4) and a drain region (5) both situated below the surface of the substrate, respectively on two opposite sides of the gate electrode (1). The source region and the drain region each comprise a portion of a second semiconductor material (6, 7) disposed on the substrate (100) and extending between the substrate (100) and the spacer (3). The second material has a melting point lower than the melting point of the first material. The portions of second material (6, 7) constitute extensions of the source (4) and drain (5) regions. The semiconductor device can be an MOS transistor.